

MicroComm



Description

The FDH-440 Full Duplex Handset Stations allows the user to talk and listen simultaneously with a master station handset or another full duplex handset sation. An optional internal speaker/ microphone allows half duplex hands free operation. These units are ruggedly constructed and include an armored handset cable with strain reliefs on each end.

The FDH-440 may be ordered with one or two optional switch, one of which can be used as a volume control. The volume switch steps through 8 preset volume levels.

Full Duplex handet station are powered through the audio lines that are connected to the DXL SAB-400/401 station audio boards or the DXL SCC-400/401 station control cards.

Features


- The FDH-440 full duplex handset stations feature:
- full duplex audio channel
- two optional switches, either one can be used for volume control
- moving handset off hook can generate automatic call request signal
- function of switches defined in software configuration
- optional internal speaker/microphone for hands free • opreration
- switch closures, power and audio use two 2-wire shielded cables
- heavy duty brushed stainless steel faceplates
- optional armored handset cable
- rugged cable strain reliefs
- rugged metal handset cradle
- impact resistant handset •
- depluggable MTA100 series connectors eliminate wire ٠ stripping during servicing and installation
- mounting on standard 4 gang electrical boxes
- compatibility with all standard #6-32 mounting hardware allowing any type of security screw to be used

Full Duplex Handset Station



Specifications

Physical	8.125" W x 4.5" H x 1.75" D
	(206 mm x 114mm x 45 mm)
Faceplate	
Heavy duty	11 ga brushed stainless steel
Environmental	
Operating temperature	32 to 122 °F (0 to 50 °C)
Storage temperature	-40 to 158 °F (-40 to 70 °C)
Humidity	0 to 95 % non-condensing
Field Connections	4 pin MTA100 connector
Cabling	2 22 ga shielded twisted pair



Ordering Information

В

Part number FDH-440-ABC-DEF

- A faceplate options
 - 2 4 gang heavy duty (11 guage)
 - 9 custom (add H x W x ga to part number)
 - handset switch
 - 0 none
 - 1 handset switch
- C handset cable cord
 - 1 6 foot coiled cord
 - 2 20 inch armored
 - 3 32 inch armored
 - 4 48 inch armored
 - 6 72 inch armored (special order)
- D hook switch
 - 0 none

- 1 hook switch in cradle
- E push switches
 - 0 none
 - 1 one (Switch B)
 - 2 two (switch B and switch A)
- F internal loudspeaker/microphone
 - 0 none
 - 1 waterproof

Document # DS-FDH-440-1.11 • Copyright © 2000 Harding Instrument Co. Ltd. • All Specifications subject to change without notice • Printed in Canada



9564 Yellowhead Trail NW Edmonton, AB T5G OW4 sales@harding.ca Tel 780.462.7100 Fax 780.450.8396 www.harding.ca





Represented by: