

MicroComm DXI

MAI-120 Master Audio Interface

Description

The MAI-120 Master Audio Interface provides audio communication circuitry and control between the DXI exchange and a remote location requiring master station device interfaces. It's circuitry is an integral component of the rack mount and desk top digital intercom master stations, but must be ordered as a separate component when ordering digital panel mount versions.

Terminals are available for connection of a loudspeaker, microphone, telephone handset and hook switch, headset, and phantom powered microphone. Keyboard/display and I/O ports are connectorized.

Features

- 1 watt 45 Ω loudspeaker interface
- electret microphone interface
- phantom powered input for amplified microphones
- telephone handset interface with PTT input
- telephone hook switch interface to activate handset
- headset interface with jack switch to detect headset connection
- 2 LED's indicate network status
- 3 LED's indicate operating status
- can be connected or removed while the system is operating without disrupting the rest of the system
- internal fuse protects circuitry
- network pass through to panel mount master station



Specifications

Physical 9" H x 6.5" W x 1.8" D (229 x 165 x 46 mm)

Environmental

Operating Temperature 32 to 122 °F (0 to 50 °C) Storage Temperature -4 to 158 °F (-20 to 70 °C) Humidity 0 to 95 % non-condensing

Power Supply +12 Vdc ±10% +24 Vdc +10% - 40%

Field Connections

Network, Power, Audio DB-25 Keyboard/Display ribbon header

Handset with 6 position terminal block

Hook Switch MTA-100-8 Speaker/Microphone MTA-100-4 Phantom Powered Microphone MTA-100-4 Headset/Jack Switch MTA-100-8

Cabling

Audio 2 22 ga shielded twisted pairs Network 1* 22 ga unshielded twisted pair


Power 2* 22 ga pair


* Double for redundant wiring Handset 1 SP 2 UP provided with handset

Hook Switch 22 ga 5 conductors

Speaker 22 ga 1UTP
Microphone 22 ga 1 STP
Headset/Jack Switch 22 ga
Microphone 22 ga 1 STP
Standard FCC Part 15

Mechanical





Ordering Information

Part number MAI-120-A

A power supply options

1 12 Volt 2 24 Volt

Accessories

Panel mount loudspeaker and microphone assembly

Panel mount gooseneck microphone

Headset with boom microphone

Telephone handset with press to talk bar, cradle, and hook switch

SERRED SUALTY OF