



# MicroComm



MAI-420

## Master Audio Interface

### Description

The MAI-420 Master Audio Interface provides audio communication circuitry and control between a DXI or DXL exchange and a remote location requiring a flush mount master station with an MAI-130 keypad/display module.

Connections are available for interfacing to a loudspeaker, microphone, telephone handset and hook switch, headset, external PTT switch, phantom powered microphone.

### Features

- 1 watt 45 ohm loudspeaker interface
- electret microphone interface
- phantom powered input for amplified microphones
- telephone handset interface with PTT input
- hook switch interface to activate handset
- headset interface with jack switch to detect headset connection
- 2 LED's indicate network status
- 3 LED's indicate operating status
- can be connected or removed while the system is operating without disrupting the rest of the system
- internal fuse protects circuitry
- network pass through to panel mount master station



### Specifications

Physical 9" H x 6.5" W x 1.8" D  
(229 x 165 x 46 mm)


Environmental  
Operating Temperature 32 to 122 °F (0 to 50 °C)  
Storage Temperature -4 to 158 °F (-20 to 70 °C)  
Humidity 0 to 95 % non-condensing

Power Supply +12 Vdc ±10% @ 500 mA max  
+24 Vdc +10% - 40% @ 500 mA max

Field Connections  
Network, Power, Audio DB-25  
Keyboard/Display ribbon header  
Handset with 6 position terminal block  
Hook Switch MTA-100-8  
Speaker/Microphone MTA-100-4  
Phantom Powered Microphone MTA-100-4  
Headset/Jack Switch MTA-100-8

Cabling  
Audio 2 22 ga shielded twisted pairs  
Network 1\* 22 ga unshielded twisted pair  
Power 2\* 22 ga pair  
\* Double for redundant wiring  
Handset 1 SP 2 UP provided with handset  
Hook Switch 22 ga 5 conductors  
Speaker 22 ga 1UTP  
Microphone 22 ga 1 STP  
Headset/Jack Switch 22 ga  
Microphone 22 ga 1 STP  
Standard FCC Part 15

# Mechanical



## Ordering Information

Part number MAI-420-AB

- A power supply options
  - 1 12 Volt
  - 2 24 Volt
- B configurable hook switch interface
  - 0 none
  - 1 magnetic/mechanical configurable

## Accessories

- IMS-130 Keyboard/Display module (required)
- Panel mount loudspeaker and microphone assembly
- Panel mount gooseneck microphone
- Headset with boom microphone
- Telephone handset with press to talk bar, cradle, and hook switch



9564 Yellowhead Trail NW Tel 780.462.7100  
 Edmonton, AB T5G 0W4 Fax 780.450.8396  
 sales@harding.ca www.harding.ca



Represented by: